


COIL FORMER


General data 6-pins POT18/11 coil former


| PARAMETER | SPECIFICATION | |
|---|--|--|
| Coil former material | polyamid (PA66), glass reinforced, flame retardant in accordance with "UL 94HB"; UL file number E41938 | |
| Pin material copper-tin alloy (CuSn), tin (Sn) plated | | |
| Maximum operating temperature 130°C, "IEC 60085", class B | | |
| Resistance to soldering heat | esistance to soldering heat "IEC 60068-2-20", Part 2, Test Tb, method 1B, 350 °C, 3.5 s | |
| Soldeerability | "IEC 60068-2-20", Part 2, Test Ta, method 1 | |











Winding data and area product for 6-pins POT18/11 coil former

| NUMBER OF SECTIONS | WINDING AREA (mm²) | MINIMUM WINDING WIDTH (mm) | AVERAGE LENGTH OF TURN (mm) | AREA PRODUCT Ae x Aw (mm ⁴) | TYPE NUMBER |
|-----------------------|--------------------------|-------------------------------------|--------------------------------------|--|------------------|
| 1 | 18 | 2*2.85 | 37 | 775 | POT-1801-1-2S-6P |

| Dimensions: (mm) | REMARK | | |
|------------------|--------------------|-----------------------------------|--|
| | Mould No.: POT1801 | Bobbin material: PA66 | |
| | Code No.: FAY01091 | Available for Fuan core: POT18/11 | |



Fuan Electronics

TEL :0086-514-87693589 EML :sales@fuantronics.net WEB:www.fuantronics.net

| Make: P.Xiao | Material Number: A4C180110100 |
|-----------------------|-----------------------------------|
| Checked: Beson. zhan | Document/Rev: 00 |
| Approved: Anson. zhan | Date of Recognition: Oct./23/2019 |