



СВЕТОДИОДЫ ЦИЛИНДРИЧЕСКИЕ 3.0 мм

LED LAMP SPECIFICATION

Type	Part Number	Emitting Color	Chip Material	Lens - color	Wave Length (nm)	Luminous Intensity (mcd) @ If = 10mA Min. Max.	Operating & Storage Temp.(°C) Range	View Angle (deg) 2θ 1/2	Package Dimension Tolerance: ±0.25 (0.01) Unit: mm (inch)
------	-------------	----------------	---------------	--------------	------------------	---	-------------------------------------	-------------------------	---

3mm/Cylindrical	3R4PD-16	Red	GaP	Red Diffused	700	0.4 ~ 3.5	-40 ~+85	100	
	3R4HD-16	High Red	GaAsP/GaP	Red Diffused	635	3.5 ~ 12.0	-40 ~+85	100	
	3O4HD-16	Orange	GaAsP/GaP	Orange Diffused	590	1.0 ~ 7.5	-40 ~+85	100	
	3G4HD-16	Green	GaP	Green Diffused	568	1.0 ~ 7.5	-40 ~+85	100	
	3Y4HD-16	Yellow	GaAsP/GaP	Yellow Diffused	590	1.0 ~ 7.5	-40 ~+85	100	

3mm/Cylindrical	3R4HC-17	High Red	GaAsP/GaP	Water Clear	635	3.5 ~ 12.0	-40 ~+85	125	
	3G4HC-17	Green	GaP	Water Clear	568	1.8 ~ 7.0	-40 ~+85	125	
	3Y4HC-17	Yellow	GaAsP/GaP	Water Clear	590	1.8 ~ 7.0	-40 ~+85	125	
	3R4HT-17	High Red	GaAsP/GaP	Red Transparent	635	3.5 ~ 12.0	-40 ~+85	125	
	3G4HT-17	Green	GaP	Green Transparent	568	1.8 ~ 7.0	-40 ~+85	125	
	3Y4HT-17	Yellow	GaAsP/GaP	Yellow Transparent	590	1.8 ~ 7.0	-40 ~+85	125	