



Top View of Assembly SECTION A-A End View of Assembly









SECTION B-B Side View of Assembly





Top View Looking Inside Box

Lid 205.00 [8.071] 79.50 103.30 [3.130] (Center Distance) [4.067] 183.50 [7.224]



Enclosures can be Factory Modified (Milling, Drilling, Printing etc.)

Contact Factory mjm@hammondmfg.com for quotes Solid models of this enclosure available in STEP or IGES.

NOTE

Purchased assembly includes box, lid and 6 cover screws. Box and lid are made from Diecast Aluminum Alloy (alloy type 380). Silicone Gasket Loctite #5950

,	
PART NUMBERS	
1590R1FL Enclosure	
Unfinished	1590R1FL
Grey Textured Polyester Powder Paint - RAL 7038	1590R1FLGY
Black Textured Polyester Powder Paint - RAL 9011	1590R1FLBK
1590R1FL Liquid Resistant Enclosure (Silicon Factory Installed Gasket)	
Unfinished	1590W R1FL
Black Textured Powder Paint	1590WR1FLBK
ACCESSORIES	
Recommended Torque: 75 ozf.in / 55 cN.m	
Black Textured Cover Screws (Pkg 50) [6-32 x 1/2" SS Type 304]	1590WMS100BK
Unfinshed Cover Screws (Pkg 100) [6-32 x 1/2" Nickel Plated Screws]	1590WMS100
Standard Cover Screws	
Unfinshed Cover Screws (Pkg 100) [6-32 x 1/2" Nickel Plated Screws]	1590MS100
Black Textured Cover Screws (Pkg 50) [6-32 x 1/2" SS Type 304]	1590MS100BK
HAMMOND	

MAINUFACTURING TM

1590R1FL

www.hammondmfg.com