
1. FOR TV/VCR

Part Number	Center Frequency fn (MHz)	3dB Bandwidth (KHz) min	20dB Bandwidth (KHz) max	Insertion Loss (dB) max	Spurious Attenuation (dB) min
LT4.5MB	4.5	fn±60	530	6	20(4.5+0.8MHz) 20(4.5-1.0MHz)
LT5.5MB	5.5	fn±75	550	6	25(5.5±1.0MHz)
LT6.0MB	6.0	fn±80	600	6	25(6.0±1.0MHz)
LT6.5MB	6.5	fn±80	630	6	25(6.5+1.0MHz) 30(6.5-1.0MHz)

2. LOW SPURIOUS IN PICTURE BAND TYPE

Part Number	Center Frequency fn (MHz)	3dB Bandwidth (KHz) min	20dB Bandwidth (KHz) max	Insertion Loss (dB) max	Spurious Attenuation (dB) min
LTSH4.5MCB	4.5	fn±60	600	6	30(0-fn)
LTSH5.5MCB	5.5	fn±60	600	6	30(0-fn)
LTSH6.0MCB	6.0	fn±60	600	6	30(0-fn)
LTSH6.5MCB	6.5	fn±70	650	6	30(0-fn)
LTSH4.5MDB	4.5	fn±70	750	6	30(0-fn)
LTSH5.5MDB	5.5	fn±80	750	6	30(0-fn)
LTSH6.0MDB	6.0	fn±80	750	6	30(0-fn)
LTSH6.5MDB	6.5	fn±80	800	6	30(0-fn)

3. HIGH SELECTIVITY SERIES

Part Number	Center Frequency fn (MHz)	3dB Bandwidth (KHz) min	20dB Bandwidth (KHz) max	Insertion Loss (dB) max	Spurious Attenuation (dB) min
LTT5.5MA	5.5	fn±50	350	9	50(5.5±1.0MHz)
LTT5.74MA	5.74	fn±50	350	9	50(5.74±1.0MHz)
LTT6.0MA	6.0	fn±50	400	9	50(6.0±1.0MHz)
LTT6.5MA	6.5	fn±50	400	9	50(6.5±1.0MHz)

4. DIMENSION

