



REV	CONTENT	CHK	DATE
V0.0	CONTENT	DLL	20.05.11

Electrical :

- | | | |
|--|------------------|------------------------|
| | UL | IEC |
| 1.Rated Voltage : | 300V | 250V |
| 2.Rated Current : | 15A | 18A |
| 3.Torque Value : | M2.5 , 3.54Lb.in | M2.5 , 0.4N.m |
| 4.Wire Range: | 28-12AWG | 0.5-2.5mm ² |
| 5.Stripping Length : | 5-6mm | |
| 6.Withstanding Voltage : | AC2000V/1Min. | |
| 7.Operating Temperature : | -40°C~+105°C | |
| 8.RoHS Compliance | | |
| 9.Safety Approval : | | |
| 10."★" is the key quality control point. | | |



- GT632 - 5.0 - 36P - 11 - 00
- | | | | | | |
|---------------|-------|---------------|------------------------------------|-----------------------------------|---|
| ① | ② | ③ | ④ | ⑤ | ⑥ |
| Series No. | Pitch | Poles | ④ 1 Single Pitch
2 Double Pitch | ⑤ Color: | |
| 02 02Contacts | | 03 03Contacts | | 1 Grey | |
| ... | | 36 36Contacts | | 2 Blue | |
| | | | | 3 Black | |
| | | | | 4 Green | |
| | | | | 5 Orange | |
| | | | | 6 Red | |
| | | | | 7 Transparent | |
| | | | | 8 Yellow | |
| | | | | 9 White | |
| | | | | ⑥ Customer Request : 00--Standard | |

5	Screws	XXXXXX	36	Steel	Zn plated
4	Cage	XXXXXX	36	Steel	Zn plated
3	Contacts	XXXXXX	36	copper alloy	Sn plated
2	Cover	XXXXXX	1	PC	UL94V-0
1	Housing	XXXXXX	1	PC	UL94V-0
ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTE
DWG.	DLL	DATE	20.05.11	SIZE	A4 UNITS mm SHEET/OF 1 / 1
CHK.		DATE		SCALE	1:1
APP.		DATE		NAME	GT632-5.0-36P-11-00
				DWGNO.	XXXX

A	Total Pitch Tolerances in mm									Nominal dimension range in mm																
	over 0	over 30	over 53	over 70	over 90	over 115	over 150	over 250	over 350	over 0	over 30	over 53	over 70	over 90	over 115	over 150	over 200	over 250	over 0	over 10	all	over 0	over 100	over 150		
	to 30	to 53	to 70	to 90	to 115	to 150	to 250	to 350	to 500	to 30	to 53	to 70	to 90	to 115	to 150	to 200	to 250	to 320	to 10	to 10		to 100	to 150			
	±0.18	±0.20	±0.25	±0.3	±0.35	±0.44	±0.60	±0.70	±0.85	±0.20	±0.25	±0.30	±0.35	±0.44	±0.55	±0.70	±0.80	±0.90	0.2	0.3	0.3	0.2	0.3	0.5		