















Approval			
<b>Electrical</b>			
Standard	<b>UL</b>	<b>IEC</b>	
Voltage	-	-	
Current	6.3A	6.3A	
Wire size	22-12AWG	0.5-4.0mm <sup>2</sup>	
T/W/End plate		8/58/1.5mm	
Height(NS35:7.5/NS35:15/NS32)		44/51.5/45.5mm	
Rated surge voltage/Contamination class		6KV/3	
Stripping length		8mm	
Screw thread/Tightening torque		M3.5/0.8N.m/7.0Lb-in	
Insulating material/Inflammability class		PAV-0	
Specification		Model	Pieces
(1)Terminal block		MKK 1/LD	100
(2)Cover		D-MKK 1/LD	100
(3)Partition plate			
(4)Separating plate			
(5)Cross connection links			
(6)Protective covers			
(7)Test plug			
(8)Lockout device			
(9)Test plug		TH	100
(8)Zack strip		DEK 6	

### HOW TO ORDER :

	-			<b>P</b>	-	<b>1</b>		-	X X X Customer Request	
Series No.		No. of pole				Color				
		1	2	3	4	5	6	7	8	9
		Gray	Blue	Black	Green	Orange	Red	Transp-arent	Yellow	white

	 <b>DEGSON ELECTRONICS CO., LTD.</b>
	<b>NAME</b> <b>MKK 1/LD</b>