


REVISION RECORD				
REV	ECO	DESCRIPTION	DRFT	DATE

Notes:

- Rated voltage/current:UL1059 600V 20A  
IEC 800V 32A
- Operation temperatures:-40° C~+105° C
- Withstanding Voltage: AC3000V/1Min
- Insulation Resistance:5000MΩ/DC1000V
- Wire Range: 28~12AWG 4mm<sup>2</sup>
- Undimensioned Tolerances:

Pitch range in mm		Nominal dimension range in mm						—
to	over	to	over	to	over	to	to	
6	6	10	10	6	30	90	200	∩
6	10	24	24	6	30	90	200	◇
±0.10	±0.15	±0.25	±0.1	±0.2	±0.3	±0.5	±0.7	0.05/10



3	WS 4-SD Current Carrier	6061B00010(H)	1	Copper	SnCe plated
2	WS 4-SD Spring	X00000600(H)	2	Stainless steel	

ITEM	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTES								
1	WS 4-SD Housing	6061A0Y01A(H)	1	PA66	UL94V-0								
<table border="1"> <tr> <td>DATE</td> <td>05/02/08'</td> </tr> <tr> <td>DATE</td> <td></td> </tr> <tr> <td>DATE</td> <td></td> </tr> <tr> <td>DATE</td> <td></td> </tr> </table>						DATE	05/02/08'	DATE		DATE		DATE	
DATE	05/02/08'												
DATE													
DATE													
DATE													
<p>DEGSON 宁波高正电子有限公司 DEGSON ELECTRONICS CO., LTD</p>													
NAME													
WS 4-SD-01P-1Y-00A(H)													
DRAWING NO. WS 4-SD-E01				SIZE	REV								
/PART NO.				A3	TO								
DO NOT SCALE DRAWING				SHEET 1	OF 1								