


# ST 2SC3202

## NPN Silicon Epitaxial Planar Transistor

for switching and general purpose applications.

The transistor is subdivided into two groups, O and Y according to its DC current gain.

On special request, these transistors can be manufactured in different pin configurations.




1. Emitter 2. Collector 3. Base  
TO-92 Plastic Package

### Absolute Maximum Ratings ( $T_a = 25^\circ\text{C}$ )

Parameter	Symbol	Value	Unit
Collector Base Voltage	$V_{CBO}$	35	V
Collector Emitter Voltage	$V_{CEO}$	30	V
Emitter Base Voltage	$V_{EBO}$	5	V
Collector Current	$I_C$	500	mA
Emitter Current	$I_E$	-500	mA
Power Dissipation	$P_{tot}$	625	mW
Junction Temperature	$T_j$	150	°C
Storage Temperature Range	$T_{stg}$	- 55 to + 150	°C

### Characteristics at $T_a = 25^\circ\text{C}$

Parameter	Symbol	Min.	Typ.	Max.	Unit
DC Current Gain at $V_{CE} = 1 \text{ V}$ , $I_C = 100 \text{ mA}$	$h_{FE}$	70	-	140	-
Current Gain Group O Y	$h_{FE}$	120	-	240	-
at $V_{CE} = 6 \text{ V}$ , $I_C = 400 \text{ mA}$	$h_{FE}$	25	-	-	-
	$h_{FE}$	40	-	-	-
Collector Base Cutoff Current at $V_{CB} = 35 \text{ V}$	$I_{CBO}$	-	-	0.1	μA
Emitter Base Cutoff Current at $V_{EB} = 5 \text{ V}$	$I_{EBO}$	-	-	0.1	μA
Collector Emitter Saturation Voltage at $I_C = 100 \text{ mA}$ , $I_B = 10 \text{ mA}$	$V_{CE(sat)}$	-	0.1	0.25	V
Base Emitter Voltage at $V_{CE} = 1 \text{ V}$ , $I_C = 100 \text{ mA}$	$V_{BE}$	-	0.8	1	V
Transition Frequency at $V_{CE} = 6 \text{ V}$ , $I_C = 20 \text{ mA}$	$f_T$	-	300	-	MHz
Collector Output Capacitance at $V_{CB} = 6 \text{ V}$ , $f = 1 \text{ MHz}$	$C_{ob}$	-	7.0	-	pF



**SEMTECH ELECTRONICS LTD.**  
Subsidiary of Sino-Tech International (BVI) Limited



Dated : 07/12/2002